

# HT 400S Niska pješačka barijera



# HT 400S Specifikacije

|   |  |
|---|--|
| <b>Power Requirements</b>                               | 110/220V. 60/50Hz. AC (%±10) 24V. DC -At standby ~11W. During operation ~ 60W  |
| <b>Dimensions</b>                                       | 1490 x 1220 x 2180 mm  |
| <b>Arms</b>   | A pair of, four-section (90°) rotors. Each section contains five Ø40mmx2mm, 304-Grade (Opt. 316-Grade) Stainless steel (Opt. Ø42 and Ø45mm) arms.  |
| <b>Body Features</b>                                    | Constructed on main carriers, supported by tubular profiles on lateral panels. 304- Grade stainless steel material (Opt. 316-Grade stainless steel). Top cover is protected against water for outdoors use, functionally complemented by side separator panels. Front panel and side separator panels are made of tempered glass or vertical stainless steel bars depending on choice.       |
| <b>Indicator Features</b>                               | On the front panels, graphical RGB dot matrix status displays of Green Arrow and Red Cross are provided as standard feature.   |
| <b>Operating Temperature, Humidity, IP Rating, MCBF</b> | -20°C to +68°C (Opt. -50°C with heater unit) / RH 95% non-condensing / IP 54 Outdoor Model (Opt. IP 56) / 1M Cycles  |
| <b>Control System</b>                                   | All inputs are opto-coupler protected .Controlled by dry contact or grounding input. Compatible with all access control systems that provide dry contact or grounding outputs. Optional RS232/RS485/TCP IP control module is available.  |
| <b>Operation</b>  | Manually operated bi-directional system (optional motorized) with dip switch selectable operational modes including controlled access on both-sides, one side free exit and restricted access modes.   |
| <b>Output Data</b>                                      | The system provides dry contact passage feedback by relays.  |
| <b>Emergency Mode</b>                                   | The rotor spins freely to allow free passage (Fail Safe default). Fail lock option is available.   |
| <b>Flow Rate</b>  | Passage Capacity of Mechanical unit for Manual Version= ~ 60 people/minute; Nominal= ~10-25 people/minute. (Recommended reference figure) ⚠ Please note that; the above given figures are approximations for one person per walkway or lane.   |
| <b>Standard Features</b>                                | LED direction and status indicators  |
| <b>Optional Accessory and Applications</b>              | Remote control units (RF or with cable), interface unit for PC, RS485, RS232 and LAN, counter, audio-messaging system, floor mounting plate, coin slot/ intelligent coin system and coin box, card reader pole, seat limiter for stadium solutions, animated indicators, internal battery and charge unit, motor driven unit, heater positive unit, separators, card reader mounted bracket. |

# HT 400S Tehnički nacrt

