

WG 5 Pješačka barijera



WG 5 Specifikacije

Power Requirements	WG 5 ; 110/220 V. 60/50 Hz. AC (%±10) 24 V. DC at standby ~7,5W max. ~27,4W. WG 5 FW ; 110/220 V. 60/50 Hz. AC (%±10) 24 V. DC at standby ~15W max. ~27,4W
Wing Features	Available in 900 mm standard length. Ø40 mm x 2,5 mm 304-Grade stainless steel wing frame and acrylic infill. (Opt. 450 mm - 600 mm - 1200 mm wing length). (900 mm and 1200 mm wings with acrylic infill are for indoor use only.)
Body Features	1,5 mm 304-Grade (Opt. 316-Grade) stainless steel with brushed (Opt. Satin) surface.
Operating Temperature, Humidity, IP Rating, MCBF	-20°C to + 68°C (Opt. -50°C with heater unit), RH 95% non-condensing / IP 54 Outdoor Model (Opt. IP 56) / 1M Cycles
Control System	All inputs are opto-coupler protected. Compatible with all access control systems that provide dry contact or grounding outputs. Optional RS232/RS485/TCP IP control module is available.
Operation	Electronically controlled DC motor driven bi-directional system.
Emergency Mode	System allows free passage in emergency mode and in case of power failure. For WG 5 FW Only; As it is equipped with magnetic locking mechanism, gate opens easily by pushing in case of emergency. Optionally available to comply with German Emergency Exit Regulation.
Flow Rate	Wing Opening / Closing Time ~1,5 - 2,5 sec.
Standard Features	RBG LED Status indicator.
Optional Accessory and Applications	Remote control unit, interface unit for PC, RS485, RS232 and LAN, counter, audio-messaging system, floor mounting plate, separator, card reader pole, customized top covers to accommodate various accessories.

WG 5 Tehnički nacrt

