

602D Tripod pješačka barijera



602D Specifikacije

Power Requirements	110/220V. 60/50Hz. AC (%±10) 24V. DC at standby ~11W. max. ~60W
Dimensions	450x1000x300 + arm length (470mm)
Arms	Ø40mmx2mm 304-Grade (Opt. 316-Grade) Stainless steel (Opt. anodised hard aluminium). Arms can be dismantled or mounted one by one separately.
Body Features	304-Grade (Opt. 316-Grade) Stainless steel with brushed (Opt. Satin) surface protected against water for outdoors use.
Indicator Features	Green Arrow & Red Bar LED
Operating Temperature, Humidity, IP Rating, MCBF	-20°C to +68°C (Opt. -50°C with heater unit) / RH 95% non-condensing / IP 54 Outdoor Model (Opt. IP 56) / 1M Cycles
Control System	All inputs are opto-coupler protected. Controlled by dry contact or grounding input. Compatible with all access control systems that provide dry contact or grounding outputs. Optional RS232/RS485/TCP IP control module is available.
Operation	Bi-directional passage, manually (Opt. Motorized) operated system
Output Data	The system provides dry contact passage feedback by relays.
Emergency Mode	(Standard: Fail Safe); in case of power failure or emergency, the arms free themselves to allow free passage (Opt. Fail Secure).
Flow Rate	Capacity of Mechanism (Manual System): ~90 passages/minute; Nominal: ~25 - 46 passage-per-minute (Recommended reference figure) Explanatory Notes: - The above given figures are approximate for one person per walkway or lane. - The system allows the new passage authorisation in less than ~0, 3 seconds. After the passage authorization, the total passage time depends on the pushing and passage speed of the people. - Utilisation of different access control units can change the flow rate.
Standard Features	Direction and status indicators on top and sides.
Optional Accessory and Applications	Remote control units, interface unit for PC, RS485, RS232 and LAN, counter, audiomessaging system, motor driven unit, automatic drop (retractable) arm, alarm sensor, heater positive unit, coin slot/intelligent coin system and coin box, card reader pole, pipe barrier (Separator), floor mounting plate.

602D Tehnički nacrt

