

FKR 777 Pješačka barijera



FKR 777 Specifikacije

Power Requirements	110/220-240V. 60/50Hz. AC (%±10) 24V.DC at standby ~13W.max. ~65W.
Dimensions	900x1150x310 + Arm length (470mm)
Arm Features	Three Ø40 mm transparent acrylic arms. Can be dismantled or mounted one by one separately. (Opt. Aluminium or stainless steel)
Body Features	The natural granite (Star Galaxy Black) stone (2cm thickness) on top is a standard feature for a decorative and aesthetical appearance. Lower body is made of Art-Line design semitransparent layered dark grey plexiglas panels.
Indicator Features	Green Arrow & Red Bar LED
Operating Temperature, Humidity, IP Rating, MCBF	-20°C - +68°C (Opt. -50°C with heater unit) / RH 95% non-condensing /IP 44 Indoor Model (IP 56 option is available for optional pipe wing versions)/ 1M Cycles.
Control System	All inputs are opto-coupler protected. Controlled by dry contact or grounding input. Compatible with all access control systems that provide dry contact or grounding outputs. Optional RS232/RS485/TCP IP control module is available.
Operation	Manually operated bi-directional system (optional motorized) with dip switch selectable operational modes including controlled access on both sides, one side free (exit or entry) and other side controlled access and access restriction modes.
Output Data	The system provides dry contact passage feedback by relays.
Emergency Mode	(Standard: Fail Safe); in case of power failure or emergency, the arms rotate freely to allow rapid passage (Opt. Fail Secure).
Flow Rate	Passage Capacity of Mechanism (Manual System):~90 passages/minute Nominal: ~25 - 46 passage-per-minute (Recommended reference figure) Explanatory Notes: - The above given figures are approximate for one person per walkway or lane. - The system allows the new passage authorisation in less than ~0, 3 seconds. After the passage authorization, the total passage time depends on the pushing and passage speed of the people. <ul style="list-style-type: none">Utilisation of different access control units can change the flow rate.
Standard Features	Direction and status indicators on top and sides.
Optional Accessory and Applications	Remote control units, interface unit for PC, RS485, RS232 and LAN, counter, audio-messaging system, motor driven unit, automatic drop (retractable) arm, alarm sensor, heater positive unit, coin slot/intelligent coin system and coin box, card reader pole, pipe barrier (Separator), floor mounting plate.

FKR 777 Tehnički nacrt

